



### Standard Equipment

- Triple-phase load break switch RV36, class E3 according to IEC 62271-103, SF<sub>6</sub>-insulation
- Integrated interlocked earthing switch with making capacity up to 50 kA
- Cable support
- Door interlock
- Sockets for capacitive voltage detector with parallel testing possibility HR/LR
- Low-voltage compartment

### Options

- Set of auxiliary contacts on load break switch
- Set of auxiliary contacts on earthing switch
- Key interlock on load break switch
- Key interlock on earthing switch
- Key interlock on both
- No door interlock
- Motor operation: 24-48-110 V - DC or 110-220 V AC
- Short-circuit indicator (to be specified by the customer when the order is placed)
- Voltage indicators
- Cubicle base: 200 mm, 300 mm or 400 mm height (Other dimensions on request)
- Floor panels
- Button press control
- Remote control

### APPLICATION

Supply cable connection.

### SPECIFICATIONS & DIMENSIONS

Rated Voltage	kV	36
Rated current	A	630
Short-term current	kA	20
Time of the short duration of current	s	3
Width	mm	418
Depth	mm	760
Height	mm	1790
Height between ground and end socket	mm	790
Height between ground and cable support	mm	310
Weight	kg	225
IAC AFL		16kA - 1s